





7300 Aluminum Foil Tape

7300 is an aluminum foil tape used for shielding. The construction is outside layers of aluminum and a center of polypropylene.105°C.

FEATURES:

- Aluminum foil
- Polypropylene film

STANDARD SIZES:

Length: 146m, 219m Width: 19mm, 25mm Core ID: 38mm



COLORS:

Natural

Other sizes and colors are available on request.





7300

Properties	Value	Unit	Test Method
Total thickness	0.040~0.05	mm	ASTM D1000
Tensile strength	>86	Мра	ASTM D1000
Elongation at break	>35	%	ASTM D1000
Flammability	B(self-extinguishing)		ISO 3795
Temperature rating	B:-40~105	°C	ES-BU5T-1A303-AA

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

Three-ply polypropylene laminate typically used in a variety of applications where EMI/FRI shielding is required.

STORAGE AND SHELF LIFE

The shelf life of the product is one year when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Avery Dennison Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is a trademark of Avery Dennison Corporation. Plyon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.



