



9524-PS-5 Protective Sleeve

High quality PET cloth in parts coated with a strong acrylic based adhesive, extra robust material longitudinal application, 125°C.

FEATURES:

PS-5(0.33mm): Double Layer

Acrylic adhesive

BENEFITS:

- Low VOC
- Stable against rotting
- High tear resistance and stability
- High temperature stability
- Enhanced abrasion resistance
- Flexible and easy to handle
- Excellent media resistance
- Available with customized perforation



STANDARD SIZES:

Length: 50m Width: PS-5: 50mm,95mm,140mm,190mm,230mm Core ID: 76.2mm

COLORS:

Black Other sizes and colors are available on request.





9524-PS-5

| Properties | Value | Unit | Test Method |
|---------------------------|-----------------------|--------|-------------------------------|
| Total thickness | | | EN 1942 |
| — double layer | 0.330±0.06 | mm | |
| Adhesion strength | | | ISO 29862 |
| — to steel | >1.5 | N/cm | |
| — to backing | >1.5 | N/cm | |
| Flammability | B(self-extinguishing) | | GMW 16740 / LV 312 |
| Abrasion resistance(φ5mm) | | | ISO 6722 / GMW 16740 / LV 312 |
| — double layer | D:1000~4999 | cycles | |
| Noise dampening | | | GMW 16740 / LV 312 |
| — double layer | A:0~2 | dB(A) | |
| Temperature rating | C:-40~125 | °C | GMW 16740 / LV 312 |

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

9524-PS-5 is especially designed for cable harnessing in the automotive industry. The longitudinal application enables a very flexible and adaptive harness covering. At the same time, the basic material of 9524-PS-5 offers a high temperature stability, enhanced abrasion resistance and excellent media resistance.

STORAGE AND SHELF LIFE

The shelf life of the product is one year when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Avery Dennison Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is a trademark of Avery Dennison Corporation. Plyon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.



Avery Dennison Yongle Tape No.9 East Yanyi Road, Industrial Park, T Zhuozhou, Hebei, P.R. China Post code: 072750

TEL: 0510-82021817 / 13921396678

For more information on our tapes and adhesive solutions, visit www.yongletape.com.cn