





MW80 Masking Tape

Masking tape with pressure sensitive adhesive, good weather-resistance, does not leave residues.

FEATURES:

- Rubber adhesive
- Paper carrier

BENEFITS:

- Pressure sensitive
- Quick paste
- Easy stripping
- Convenient writing
- Hand tearability
- Meet RoHS



STANDARD SIZES:

Length: 25m, 50m

Width: 6mm, 12mm, 12.7mm, 19mm, 38mm

Core ID: 76.2mm

COLORS:

Black White Yellow

Other sizes and colors are available on request.





MW80

Properties	Value	Unit	Test Method
Total thickness	0.140±0.01	mm	GB/T 7125-1999
Initial adhesivity (rolling ball method)	≥12	Ball no.	GB/T 4852-2002
180° Adhesion strength to steel	≥2.2	N/cm	GB/T 2792-1998
Persistent adhesivity (to steel)	≥10	h	GB/T 4851-1998
Tensile strength	≥28	N/cm	GB/T 7753-1987
Elongation at break	≤20	%	GB/T 7753-1987
Temperature resistance	80°C x 30min		

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

Suitable for masking applications at the car industry. It is applicable to vehicle painting, interior decoration, paint spraying, binding up light stuff, and eliminating velveteen, etc.

STORAGE AND SHELF LIFE

The shelf life of the product is six months when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Avery Dennison Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is a trademark of Avery Dennison Corporation. Plyon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.



